


② TŘM. ØR6ð200mm
DL. 1.00m - (45+70+70+45) = 230ks

③ TŘM.ØR6ã200mm
DL.0.74m-45ks

④ **PODÉLNÁ ZÁLIVKOVÁ VÝZTUŽ – $\varnothing R12$, STYKOVAT PŘESAHEM 600mm, V ROZÍCH PŘEVÁZAT.**
CELKEM 1x(9+14+14+9)x1,15=53,0b.m.

OZN.	Ø	DĚLKA m	KS	DĚLKA DLE Ø CELKEM			PLOCHA stř. KARI
				B500A	ØR10	B500B	Ø8x150/150
				ØR6	ØR8	ØR12	
1	R12	253,00	–			253,00	
2	R6	1,00	230	230,00			
3	R6	0,74	45	33,30			
4	R12	53,00	–			53,00	
5	R12	1,65	12			19,80	
6	R12	3,00	6			18,00	
				263,30		343,80	
CELKEM			m	0,222		0,888	
			kg	58,45		305,29	
			kg	58,45		305,29	

BETON TR. C25/30, OCEL B500A, B500B (10505-R)
KRYTÍ VÝZTUŽE 25 MM

		ASET studio architektonická a projektová kancelář	
ASET studio s.r.o. Tovární 41, 779 00 Olomouc www.asetstudio.cz		Zak. č.:	1723
		Datum:	12/2017
		Měřítko:	1:50
		Část:	Paré:
		Výkř.: b05	